

BENEFITS

AeroSpreader S250

Configured for **AeroSpreader S250 (250 kg (33x36x44), AB135 Pull Start 6.5HP, 4" SS Flex Handheld Hose, No Rotate Motor, No Extension Tube, No Gull Wing, Simple Controls, Stationary Skid 250, No Inlet Silencer)**



WHY IT MATTERS

Benefits

How the selected equipment supports feed placement, operator control and installation requirements.



Controlled feed distribution

Pneumatic conveying and broadcasting support controlled distribution of dry fish-feed pellets.



Adaptable installation

The S250 offering supports truck, trailer or vessel installation planning. Select the mobility and mounting arrangement appropriate to the installation.



Equipment matched to the application

A choice of broadcast equipment and controls allows the offering to be configured around the operating requirements. Optional equipment is supplied only when selected.



Metering — Manual

Keep feed-delivery adjustment under direct operator control during feeding.



Hopper Capacity — 250 kg (33x36x44)

Choose the hopper arrangement around the available installation space while retaining nominal 250 kg feed storage.



Engine — AB135 Pull Start 6.5HP

Manual pull starting provides a straightforward operator-started engine arrangement.



Broadcast — 4" SS Flex Handheld Hose

Give the operator direct control of outlet placement using a flexible handheld feed hose.



Control Type — Simple Controls

Keep blower-speed and feed-delivery adjustments at the machine.



Mobility — Stationary Skid 250

Use a stationary mounting arrangement for a fixed installation on the intended platform, vessel or site.