

SPECIFICATIONS

AeroSpreader S1000

Configured for **AeroSpreader S1000 (1-Chamber, AB135 TEFC-Electric w/7.5hp Frequency Drive, Manual, 4" Manual Periscope Feed Head, No Extension Tube, No Gull Wing, Cable Controls 1000&above, No Enclosure Panels, No Rotate Motor, Stationary, No Bulk Bag Safety Ring, No Bulk Bag Cutter, 4inch eductor, M100, AB135 Inlet Silencer (6.5 hp))**



TECHNICAL OVERVIEW

Specifications

AeroSpreader S1000 is a configurable pneumatic aquaculture feed broadcaster with a nominal 1,000 kg marine-aluminum hopper and Slide & Stow lid. Select the available metering, blower, broadcast equipment, controls and mounting arrangement for the feeding operation. Manual metering, volumetric metering and load-cell weighing are distinct arrangements; weighing and automation are included only when explicitly specified. Feed rate and coverage depend on the selected equipment and pellet properties.



Nominal hopper capacity

1,000 kg. Usable feed mass depends on pellet bulk density and the loading arrangement.



Configuration and performance

Blower, metering, outlet and controls follow the selected equipment. Feed rate and coverage depend on pellet properties and operating conditions.